

## Solis-(80-110)K-5G-PRO

# Solis Three Phase Inverters

### Efficient

- 6/8 MPPTs, max. efficiency 98.5%
- > 150% DC/AC ratio
- Compatible with bifacial modules

### Smart

- Night SVG function
- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation

### Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Globally recognised branded componentry for longer life

### Economic

- Power line communication (PLC) (optional)
- DC side supports "Y" connector
- Supports aluminium wire access to reduce cost

### Models:

Solis-80K-5G-PRO

Solis-100K-5G-PRO

Solis-110K-5G-PRO



## DATASHEET

## Solis-(80-110)K-5G-PRO

Models	80K	100K	110K
<b>Input DC</b>			
Max. input voltage		1100 V	
Rated voltage		600 V	
Start-up voltage		180 V	
MPPT voltage range		160-1000 V	
Max. input current	36 A / 32 A / 36 A / 32 A / 36 A / 32 A	36 A / 32 A / 36 A / 32 A / 36 A / 32 A / 36 A / 32 A	
Max. short circuit current	6*50 A	8*50 A	
MPPT number/Max. input strings number	6/12	8/16	
<b>Output AC</b>			
Rated output power	80 kW	100 kW	110 kW
Max. apparent output power	88 kVA	110 kVA	121 kVA
Max. output power	88 kW	110 kW	121 kW
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V		
Rated grid frequency	50 Hz / 60 Hz		
Rated grid output current	121.6 A / 115.5 A	152.0 A / 144.3 A	167.1 A / 158.8 A
Max. output current	133.7 A	167.1 A	183.8 A
Power factor	>0.99 (0.8 leading - 0.8 lagging)		
THDi	<3%		
<b>Efficiency</b>			
Max. efficiency		98.5%	
EU efficiency		98%	
<b>Protection</b>			
DC reverse-polarity protection		Yes	
Short circuit protection		Yes	
Output over current protection		Yes	
Surge protection		DC Type II / AC Type II	
Grid monitoring		Yes	
Anti-islanding protection		Yes	
Temperature protection		Yes	
Strings monitoring		Yes	
I/V Curve scanning		Yes	
Integrated AFCI (DC arc-fault circuit protection)		Yes <sup>(1)</sup>	
Integrated DC switch		Yes	
<b>General Data</b>			
Dimensions (W*H*D)		1183*585*363 mm	
Weight	77 kg	93 kg	
Topology	Transformerless		
Self-consumption (night)	<2 W		
Operating ambient temperature range	-30 ~ +60°C		
Relative humidity	0-100%		
Ingress protection	IP66		
Cooling concept	Intelligent redundant fan-cooling		
Max. operation altitude	4000 m		
Grid connection standard	G99, IEC61727, EN50549-1/2, VDE4110		
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4		
<b>Features</b>			
DC connection	MC4 connector		
AC connection	OT terminal (max. 240 mm <sup>2</sup> )		
Display	LCD		
Communication	RS485, Optional: Wi-Fi, GPRS, PLC		

(1) Activation required.